

H3000 LIGHT OUTPUT CHART READINGS AT 400 ASA

Speed (max)	SPOT			FLOOD		
	0,6 m	0,9 m	1,2 m	0,6 m	0,9 m	1,2 m
120	22 ₅	16 ₉	16 ₃	16 ₃	11 ₂	8.0 ₆
130	22 ₃	16 ₆	16	16 ₁	11 ₁	8.0 ₂
150	22 ₁	16 ₃	11 ₇	11 ₉	8.0 ₈	8.0
160	16 ₈	16 ₁	11 ₅	11 ₆	8.0 ₅	5.6 ₇
200	16 ₆	11 ₉	11 ₃	11 ₄	8.0 ₃	5.6 ₆
210	16 ₄	11 ₇	11 ₁	11 ₂	8.0 ₁	5.6 ₃
230	16 ₁	11 ₄	8.0 ₇	8.0 ₉	5.6 ₈	5.6 ₁
240	11 ₈	11 ₁	8.0 ₅	8.0 ₆	5.6 ₅	4.0 ₈
290	11 ₇	11	8.0 ₄	8.0 ₅	5.6 ₄	4.0 ₆
320	11 ₄	8.0 ₈	8.0 ₁	8.0 ₂	5.6 ₂	4.0 ₅
340	11 ₂	8.0 ₅	5.6 ₉	8.0	4.0 ₉	4.0 ₂
360	8.0 ₉	8.0 ₂	5.6 ₆	5.6 ₇	4.0 ₆	2.8 ₉
560	8.0	5.6 ₃	4.0 ₇	4.0 ₈	2.8 ₇	2.8
580	5.6 ₈	5.6 ₁	4.0 ₅	4.0 ₆	2.8 ₅	2.0 ₈
640	5.6 ₅	4.0 ₈	4.0 ₂	4.0 ₃	2.8 ₂	2.0 ₅
650	5.6 ₂	4.0 ₅	2.8 ₉	4.0	2.0 ₉	2.0 ₂